## **PLUGS & SOCKETS**

## **BANANA PLUGS & SOCKETS**

Banana plug 4mm. Metal pin and plastic handle -screw terminating




# Banana plug 4mm. Metal pin and plastic handle -solder terminating





Banana plug 4mm. With link hole side entry for piggy backing. Metal pin and plastic handle -screw terminating



Banana plug 4mm. Gold Plated screw terminating, side stackable.

Col Part Number BP4G.B Black BP4G.R Red



#### STACKABLE BANANA PLUGS

4mm Banana Plug with screw connec-tion for wire termination. Rear stacking allowing multiple connectors on one line. 3A @ 125V AC

IIIIe. JA @ 125	V AC	
Part Number	Colour	
BP4DS.B	Black	
BP4DS.BU	Blue	
BP4DS.R	Red	
BP4DS.W	White	
BP4DS.Y	Yellow	
BP4DS.G	Green	H

# DC POWER CONNECTORS

#### DC PLUGS

Ideal for low voltage leads. Plastic handle. Strain relief. 4.2mm cable entry. Solder terminating.


Part Number	Inner Dia	Shaft
DCP7	0.7mm	9mm
DCP10	1.0mm	9mm
DCP13	1.3mm	9mm
DCP16	1.6mm	9mm
DC21	2.1mm	9.5mm
DCP21	2.1mm	14mm
DC25	2.5mm	10mm
DCP25	2.5mm	14mm
DCP31	3.1mm	9mm


#### DC LINE PLUGS METAL



#### BANANA SOCKETS

4mm banana chassis socket. Panels up to 4mm thick. Drill 9.4mm hole





Gold plated 4mm banana chassis socket. Panels up to4mm thick. Drill 3.2mm hole

Col

**B**lac

Red

Part Numb

BS4G.B

BS4G.R



#### **HIRSHMANN:** STACKABLE BANANA PLUGS


HIRSHMANN 4mm multiple spring wire plug, with shatter proof, flexible insulating sleeve and stackable side entry. Length 60mm 30Amps 60VDC

Part Number	Colour
BULA30K-100	Black
BULA30K-101	Red
BULA30K-102	Blue
BULA30K-103	Yellow
BULA30K-104	Green

## DC CHASSIS MOUNT SOCKETS

DC Chassis Mount. Metal socket. Solder terminated - with screws





DC INLINE SOCKETS DC socket inline. Solder

Terminating, 4mm cable plastic handle



## DC INLINE METAL SOCKETS



45

## SEMTRONICS P/L

#### CAPTIVE BINDING POSTS

4mm banana chassis socket Post. Panels up to 4mm thick. Drill 9.4mm hole

Colou

Red


Part Number

BS4M.B

BS4M.R



4mm banana socket and crosshole. 10A @ 125V AC. Protrusion from mounting surface 24mm. Mounting hole 8mm?.





#### HEAVY DUTY BINDING POSTS

4mm banana chassis socket Post. Panels up to 5mm thick. Drill 9.5mm hole 30Amps at 600VAC

Part Nu P9220 Black P9222 Red

#### **DUAL BINDING POSTS**

Dual 4mm banana chassis posts. Panels up to 6.5mm thick. 3.2mm mounting hole





Part Numh

DJ21P

DJ25P

Dual banana plug adaptor. Ideal for speaker posts. Accepts spades, wire and 4mm banana plugs side entry.




BP24 DC Plastic socket, Solder





DC socket chassis. All Metal. Solder terminating. 11mm Mounting hole.





DC socket chassis. Solder terminating. 8mm Mounting hole


Part Numb

P0122

P0123



DC socket chassis. Solder terminating. 12.5mm Mounting hole





#### PH (03) 9873 3555 FAX (03) 9873 3355









